

BEST AVAILABLE COPY

RECEIVED
CENTRAL FAX CENTER

FEB 20 2007

AMENDMENTS TO THE CLAIMS

The following listing of claims replaces all prior versions:

1. (Currently Amended) An apparatus comprising:

an input power port;

~~a power rail~~ an output power rail, said output power rail to supply power to
a load powered by the apparatus;

a battery unit; and

a system charger voltage regulator (VR) to couple the input power port to
the battery unit, and said battery unit to couple with the system charger VR and
the ~~power rail~~ output power rail,wherein said system charger VR is to provide a regulated voltage signal
when a power source is coupled to the input power port, said regulated voltage
signal to simultaneously power both the ~~power rail~~ output power rail and the
battery unit, andwherein said battery unit is to provide a battery voltage signal to power the
~~power rail~~ output power rail when no power source is coupled to the input power
port, and~~wherein the regulated voltage signal and the battery voltage signal have a~~
~~common upper bound and a common lower bound.~~

2. - 4. (Cancelled)

BEST AVAILABLE COPY

5. (Previously Presented) The apparatus of claim 1 wherein the power source comprises a voltage from one of an AC/DC converter, an external battery, a fuel cell, a solar panel, and power over a local area network.

6. (Currently Amended) The apparatus of claim 1 wherein the battery unit comprises:

a battery pack port to couple to the system charger VR and to receive a battery pack; and

a power source selector to selectively couple either the system charger VR to the ~~power rail~~output power rail or the battery pack port to the ~~power rail~~output power rail.

7. (Original) The apparatus of claim 6 wherein the system charger VR is to power the battery pack port to recharge a discharged battery coupled to the battery pack port.

8. (Currently Amended) The apparatus of claim 1 wherein the battery unit comprises:

a plurality of battery pack ports, each of the plurality of battery pack ports to couple to the system charger VR and to receive a battery pack; and

a power source selector to selectively couple any one of the system charger VR and the plurality of battery pack ports to the ~~power rail~~output power rail.

BEST AVAILABLE COPY

9. (Original) The apparatus of claim 8 wherein the battery unit further comprises:

a battery charging selector to couple between the system charger VR and each of the plurality of battery pack ports, said battery charging selector to selectively couple any one of the plurality of battery pack ports to the system charger VR.

10. (Currently Amended) The apparatus of claim 1 wherein the ~~power-rail~~output power rail extends beyond the battery unit to couple the system charger VR to the battery unit.

11. (Original) The apparatus of claim 10 wherein the battery unit comprises:
a battery pack port to receive a battery pack.

12. (Currently Amended) The apparatus of claim 11 wherein the battery unit further comprises:

a switch to selectively couple the battery pack port to the ~~power-rail~~output power rail.

13. (Currently Amended) The apparatus of claim 12 wherein, if the battery pack is coupled to the battery pack port, said switch is to couple the battery pack port

BEST AVAILABLE COPY

to the ~~power rail~~output power rail for either powering the ~~power rail~~output power rail or charging the battery pack.

14. (Previously Presented) An apparatus comprising:

an input power port;

a power rail;

a battery unit, wherein the battery unit includes a battery pack port to receive a battery pack; and

a system charger voltage regulator (VR) to couple the input power port to the battery unit, and said battery unit to couple with the system charger VR and the power rail,

wherein the power rail extends beyond the battery unit to couple the system charger VR to the battery unit, and

wherein the battery pack comprises:

a switch control port to receive a switch control signal from the battery pack port;

a battery stack; and

a switch to selectively couple the battery stack to the battery pack port based at least in part on the switch control signal.

15. (Original) The apparatus of claim 10 wherein the battery unit comprises:

a plurality of battery pack ports, each to receive a battery pack.

BEST AVAILABLE COPY

16. (Currently Amended) A method comprising:

generating a regulated charging voltage signal when a power source is available;

providing the regulated charging voltage signal to simultaneously power both a ~~power rail~~ an output power rail and a battery unit, said output power rail to supply power to a load powered by the apparatus; and

providing a battery voltage signal to power the ~~power rail~~ output power rail when no power source is available;

~~wherein the regulated voltage signal and the battery voltage signal have a common upper bound and a common lower bound.~~

17. (Cancelled)

18. (Original) The method of claim 16 wherein the power source comprises a voltage from one of an AC/DC converter, an external battery, a fuel cell, a solar panel, and power over a local area network.

19. (Original) The method of claim 16 wherein providing the regulated voltage signal to power the battery unit comprises:

recharging a discharged battery in the battery unit.

20. (Currently Amended) A system comprising:

a mobile computer; and

BEST AVAILABLE COPY

a power apparatus for the mobile computer, said power apparatus comprising

- an input power port;
- ~~a power rail~~ an output power rail, said output power rail to supply power to a load powered by the apparatus;
- a battery unit; and
- a system charger voltage regulator (VR) to couple the input power port to the battery unit, and said battery unit to couple with the system charger VR and the ~~power rail~~ output power rail,

wherein said system charger VR is to provide a regulated voltage signal when a power source is coupled to the input power port, said regulated voltage signal to simultaneously power both the ~~power rail~~ output power rail and the battery unit, and

wherein said battery unit is to provide a battery voltage signal to power the ~~power rail~~ output power rail when no power source is coupled to the input power port, and

~~wherein the regulated voltage signal and the battery voltage signal have a common upper bound and a common lower bound.~~

21. - 23. (Cancelled)

24. (Currently Amended) The system of claim 20 wherein the battery unit comprises:

- 8 -

Atty. Docket No.: P17639
Application No.: 10/750,568

BEST AVAILABLE COPY

a battery pack port to couple to the system charger VR and to receive a battery pack; and

a power source selector to selectively couple either the system charger VR to the ~~power rail~~output power rail or the battery pack port to the ~~power rail~~output power rail.

25. (Currently Amended) The system of claim 20 wherein the battery unit comprises:

a plurality of battery pack ports, each of the plurality of battery pack ports to couple to the system charger VR and to receive a battery pack; and

a power source selector to selectively couple any one of the system charger VR and the plurality of battery pack ports to the ~~power rail~~output power rail.

26. (Original) The system of claim 25 wherein the battery unit further comprises:

a battery charging selector to couple between the system charger VR and each of the plurality of battery pack ports, said battery charging selector, to selectively couple any one of the plurality of battery pack ports to the system charger VR.

27. (Currently Amended) The system of claim 20 wherein the ~~power rail~~output power rail extends beyond the battery unit to couple the system charger VR to the battery unit.

BEST AVAILABLE COPY

28. (Original) The system of claim 27 wherein the battery unit comprises:

a battery pack port to receive a battery pack.

29. (Currently Amended) The system of claim 28 wherein the battery pack port comprises:

a switch to selectively couple the battery pack port to the ~~power-rail~~output power rail wherein, if the battery pack is coupled to the battery pack port, said switch is to couple the battery pack port to the ~~power-rail~~output power rail for either powering the ~~power-rail~~output power rail or charging the battery pack.

30. (Previously Presented) A system comprising:

a mobile computer; and

a power apparatus for the mobile computer, said power apparatus comprising

an input power port;

a power rail;

a battery unit, wherein the battery unit includes a battery pack port to receive a battery pack; and

a system charger voltage regulator (VR) to couple the input power port to the battery unit, and said battery unit to couple with the system charger VR and the power rail,

BEST AVAILABLE COPY

wherein the power rail extends beyond the battery unit to couple the system charger VR to the battery unit, and

wherein the battery pack comprises:

a switch control port to receive a switch control signal from the battery pack port;

a battery stack; and

a switch to selectively couple the battery stack to the battery pack port based at least in part on the switch control signal.

31. (Original) The system of claim 27 wherein the battery unit comprises:

a plurality of battery pack ports, each to receive a battery pack.

32. (New) The apparatus of claim 1 wherein the regulated voltage signal and the battery voltage signal have a common upper bound and a common lower bound.

33. (New) The method of claim 16 wherein the regulated voltage signal and the battery voltage signal have a common upper bound and a common lower bound.

34. (New) The system of claim 20 wherein the regulated voltage signal and the battery voltage signal have a common upper bound and a common lower bound.